209663US-0PCT

531 Rec'd PC.

**22** JUN 2001

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

ne andt

IN RE APPLICATION OF

10/11/2/

YUKO TACHIBANA

: ATTN: APPLICATION DIVISION

SERIAL NO: NEW U.S. PCT APPLN.

(Based on PCT/JP99/07344)

FILED: HEREWITH

FOR: LAMINATE AND ITS

PRODUCTION METHOD

## PRELIMINARY AMENDMENT

ASSISTANT COMMISSIONER FOR PATENTS WASHINGTON, D.C. 20231

SIR:

Prior to examination on the merits, please amend the above-identified application as follows.

## IN THE CLAIMS

Please amend the claims as shown on the marked-up copy following this amendment to read as follows.

3. (Amended) The laminate according to Claim 1, wherein the interlayer is a layer consisting of at least one member selected from the group consisting of an oxide, a nitride, an oxynitride, a carbide and a boride.

- 4. (Amended) The laminate according to Claim 1, wherein the thickness of the interlayer is from 0.1 to 30 nm.
- 5. (Amended) The laminate according to Claim 1, wherein the metal layer is a layer containing at least one metal selected from the group consisting of silver, copper and gold.

The first time that the train of the first time that the first time that the first time that the first time that